

OCT 06 2003

FEDERAL INSTITUTE OF INDUSTRIAL PROPERTY

Selected databases
Query parameters
Query definition
Refine query
Query results
Basket
Saved queries
Statistics
Help
Proposals
Exit

Abstract Drawing

(11) Number of the patent document

2168412

(13) Kind of document

C2

(14) Document date

2001.06.10 Query

(19) Publishing country or organization

RU

(21) Application number

99115283/03

(22) Application filing date

1999.07.12

(24) Date of rights

1999.07.12

(43) Unexamined printed documents without grant

2001.06.10 Query

(46) Documents claims only available

2001.06.10 Query

(516) Edition of IPC

7

(51) Main classification IPC

B28B11/00 Query IPC

(51) Main classification IPC

E01C19/40 Query IPC

Title

ROLL-TYPE SMOOTHING MACHINE
WITH SMOOTHING DEVICE VIBRATING
IN TRANSVERSE DIRECTION

Bratskij gosudarstvennyj tekhnicheskij
universitet Query

(71) Applicant information

Mamaev L.A. Query

(72) Inventor information

Efremov I.M. Query

(72) Inventor information

Kononov A.A. Query

(72) Inventor information

Karpenko A.V. Query

(72) Inventor information

(73) Grantee (asignee) information Bratskij gosudarstvennyj tekhnicheskij
universitet Query

Abstract Drawing

DOCUMENT
to the beginning
to the end
print
TERMS
previous
next

FEDERAL INSTITUTE OF INDUSTRIAL PROPERTY

Selected databases
Query parameters
Query definition
Refine query
Query results
Basket
Saved queries
Statistics
Help
Proposals
Exit

Bibliography

Drawing

#2168412. Abstract

FIELD: construction materials. SUBSTANCE: smoothing device has rolls rotating at speed many times exceeding speed of displacement of smoothing device over surface to be smoothed, and simultaneously vibrating in direction transverse to direction of advancement of rolls. Smoothing rolls surface contacting with surface to be smoothed is made notched. Smoothing device transverse vibration motion is imparted by drive actuated by hydraulic pumping station provided with hydraulic variable-feed pump, bypass valve and filter. Pumping station actuates vibration generator, which has hydraulic engine, eccentric conical shaft, and screw providing lowering and raising of eccentric conical shaft for changing plunger pair vibration amplitude. Working fluid which is under pressure in rubber-metal sleeve imparts vibratory motions to plunger pair rigidly connected to rotating roll. Roll is rotated by belt transmission from electric engine. Smoothing machine of such construction is used for high-quality working of unhardened concrete surfaces of ferroconcrete products molded from rigid concrete mixtures to obtain required roughness grade on ferroconcrete product faces. EFFECT: increased efficiency by stabilized process and improved quality of smoothed surfaces. 2 cl, 1 dwg

DOCUMENT
to the beginning
to the end
print

Bibliography

Drawing

